

## Market Consultation Invitation – Request for Information (RFI) No. NGAPD-3004:

### Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.

## 1 Introduction

PPC (Public Power Corporation) is conducting a Market Consultation Invitation / Request for Information (RFI) process in order to formulate the requirements of a forthcoming procurement procedure for the PPC Colocation Hybrid Data Centre (AI & Cloud spaces) at the Aghios Demetrios Power Plant, Kozani, Greece.

This project involves developing a Data Center (DC) Campus in Aghios Demetrios Power Plant in Kozani, Northern Greece. The data centers will be built in phases within the area of a former Lignite yard of the existing power station. The Data Center Campus consists of multiple 75MW data center buildings of IT load for a site total of 300MW of IT load that can be expanded up to GW scale. Each building will be scaled with multiple blocks of 25MW of IT load. Phase 1 (IT deployment) includes 4x Data Center buildings of about 75MW each reaching a total of 300MW IT. Each Data Center Building consists of 6 Data Halls; 3x Data Halls AI (15-17MW) and 3x Data Halls Cloud (8-9MW) and will be initially grid interconnected at 400kV. AI rack density is assumed 105kW/rack for AI and 20kW/rack for Cloud. Design and Facility follow Uptime Institute Tier III intent.

## 2 Project Overview

### 2.1 Primary Power – Utility Substation

Primary power for the campus will be provided via a redundant (2N) utility substation. Initial build will consist of two utility transformers to provide power for data center building(s). The utility (PPC) will provide 33kV power to the data center(s). The power feeds to the facility will be run below ground, diverse paths/separation between MV rings with concrete encasement. Medium Voltage (MV) switchgear will be draw-out type and housed in dedicated equipment areas on the site near each data center building.

### 2.2 Gensets

Utility outage support to the distribution systems will be provided by LV diesel generators (prefabricated gensets) in a dedicated generator yard. Each Data Hall is served by dedicated gensets in Distributed Redundant (DR N+1) rings for IT and separate gensets for cooling loads. Each genset is independent in the Distributed

Redundancy arrangement working in partial load during normal operation and ramping up to full load in case one unit is out of service (e.g., for maintenance).

### 2.3 Critical Power Distribution

Data center will follow Distributed Redundancy Architecture with multiple MV modules in 33KV rings. The Data Center receives dual concurrently maintainable MV incomers.

Each MV module is an outdoor unit and houses a RMU and a 33/0.4kV transformer that powers the downstream LV module.

Each LV module is normally powered from a MV module transformer and during power outage from a genset (ATS). Each LV module is an outdoor unit and houses Main LV Switchgear (MDB), UPS, Lithium batteries, CRAC (N+1) and distributes power indoor in the Data Center Building (Critical IT or Cooling Equipment).

Overall, multiple power blocks are connected in MV rings via the RMU in a Distributed Redundancy (DR) architecture. IT and cooling loads are served by different dedicated power blocks separate for AI and Cloud Data Halls.

### 2.4 Critical Cooling

#### 2.4.1 AI Data Hall

The AI Data Hall critical load will be cooled by a contained water loop. The loop will reject heat to (N+1) closed-circuit fluid chillers (Adiabatic Dry Coolers). The cooling water system will be routed around the AI Data Hall in a concurrently maintainable loop. Cooling Distribution Units (CDUs) will connect to the cooling water loop with a tertiary pump and a piping loop (provided by others) connecting to liquid-cooled servers. The Adiabatic Dry Coolers have the ability to provide free and evaporative cooling. Air cooling for the AI Data Halls will be provided by water-source heat pumps (WSHP) CRAC units placed within equipment galleries on either side of the data hall. The quantity of WSHP CRAC units will be based on the air-cooled server requirements (design is 15% of room load) with N+1 installed at each data hall.

#### 2.4.2 Cloud Data Halls

The Cloud Data Hall critical loads will be cooled by air-cooled chiller plants (N+1). Air-cooled chillers located on the roof of the data hall. The chilled water system will be routed around the Cloud Data Hall in a concurrently maintainable loop. Cooling at the Cloud data hall will be supplied by (N+2) Fan Wall Units that are placed in equipment galleries at either side of the data hall.

## 3 Purpose

The main purpose of this RFI is for PPC to identify potential Technology Providers (Participants) that have the capability and capacity to provide critical MEP equipment part of Owner Furnished Contractor Installed (OFCI) scope:

- engineering services, manufacturing and procurement of critical power equipment and solutions such as Prefabricated MV Modules (RMU & Transformers), Prefabricated LV Modules (prefabricated modules incl. LV Switchgears, UPS, Lithium Batteries, Cooling and auxiliaries) and Prefabricated Gensets for on premise power back up. All prefabricated solutions shall be suitable for outdoor use (containerized).
- engineering services, manufacturing and procurement of critical cooling equipment and solutions such as Critical Cooling System for Cloud DC (incl. Fan Wall Units, Chillers) and Critical Cooling System for AI DC (incl. CDU, Adiabatic Coolers).

The integration of the OFCI equipment shall be performed by the General Contractor (GC) under a separate Contract, part of **Contractor Furnished Contractor Installed (CFCI) scope**, as described below.

In more detail, the GC shall perform the engineering, procurement and installation of all the remaining necessary equipment/services, other than the ones provided by the Technology Provider, including all civil works, in order for the OFCI equipment and solutions to be in operation and integrated into the overall Data Center Design. Data Center Design is an ongoing process and will be provided by a Specialized Independent Consultant.

**This Market Consultation Invitation / RFI refers to all potential Technology Providers complying with the categories below:**

- General Requirements
  - ü Participants in this RFI shall be companies that are manufacturers of Data Center Products (Vendors) with at least 5 years' experience in delivering solutions for Data Centers (e.g., UPS etc.).
  - ü It is not mandatory for the participants to offer solutions for all OFCI categories. Each of the participants shall comply with the General Requirements and the OFCI product Requirements applicable to the relevant OFCI offered.
  - ü It would be preferable for the participants to have in-house designer(s) certified by Uptime Institute as Accredited Tier Designer (ATD). At least one ATD foil shall be submitted with the solution proposal.
- Specific OFCI Requirements
  - ü Participants shall be manufacturers of **Prefabricated LV Modules** that are outdoor Power Solutions for Data Centers integrating LVS, UPS, Lithium Batteries, Cooling and auxiliaries. The prefabricated LV module manufacturer shall have a minimum of 5 years of experience in the manufacture and testing of prefabricated LV module for Data Center applications. A reference list of installed prefabricated LV modules in Data Centers shall be supplied with the RFI.

- Ü Participants shall be manufacturers of **Prefabricated MV Modules** that are outdoor Power Solutions for Data Centers integrating RMU, Transformer, Cooling and auxiliaries. The prefabricated MV module manufacturer shall have a minimum of 5 years of experience in the manufacture and testing of prefabricated modules for Data Center applications. A reference list of installed prefabricated modules in Data Centers shall be supplied with the RFI.
- Ü Participants shall be manufacturers of **Prefabricated Gensets** that are outdoor Critical Power Solutions for Data Centers. The manufacturer shall have a minimum of 5 years of experience in the manufacture and testing of prefabricated gensets for Data Center applications. A reference list of installed gensets in Data Centers shall be supplied with the RFI.
- Ü Participants shall be manufacturers of **Critical Cooling Solutions** for Data Centers. The manufacturer shall have minimum of 5 years of experience in the manufacture and testing of critical cooling solutions for Data Center applications. It is allowed for a manufacturer to provide a specific part of the critical cooling solution e.g., provide Fan Wall Units without supplying chillers etc. A reference list of installed critical cooling solutions in Data Centers shall be supplied with the RFI.

In addition to the former, PPC is highly interested, in order to avoid delays in procurement of long lead items related to the OFCI scope, such as:

- Prefabricated LV Modules
- Prefabricated MV Modules
- Fan Wall Units
- Air-cooled Chillers
- CDU
- Adiabatic Dry Coolers
- Transportation to Site - DDP
- Mandatory Supervision, Installation, Commissioning, Training and other Services by participants
- Provision of critical spare parts

Any information disclosed to PPC by any participant under this procedure shall be treated as confidential and shall not be made available to any other participant or third party, except only as strictly required for the basic design of the project and the preparation of the relevant RFQ and procurement procedure.

#### **Market Consultation scope:**

- Market research and evaluation of potential Technology Providers for the OFCI scope required by PPC
- Assessment of the technical and financial capacity of potential Technology Providers.

## **4 Participation Process**

Participants in this RFI process will be required to complete and submit a relevant questionnaire, as well as to sign the enclosed NDA. In case of multiple proposals by a

Technology Provider (proposals for different types of equipment), separate questionnaires must be submitted for each proposal. **All submitted documents must be signed by an authorized person of the participating company.**

The submission of the questionnaire(s) and the distribution of the RFI documents shall be carried out using the "cosmoONE" platform of the PPC Electronic Contracts System at the online address [www.cosmo-one.gr](http://www.cosmo-one.gr) or [www.marketsite.gr](http://www.marketsite.gr). Registration does not incur any costs for those interested.

Necessary condition for participation of any interested party is registration in the System. Upon successful registration, interested parties shall be provided with System Access Codes, so as to download the questionnaire(s) and NDA (in editable format). Responses (completed questionnaire(s) and signed NDA) shall be submitted by the interested parties electronically, with a start date of submission on the 2<sup>nd</sup> of February 2026 and a closing date and time of submission on the 28<sup>th</sup> of February 2026 at 16:00 (Greek time).

After the above deadline, submission of responses shall not be possible, unless PPC, at its own discretion, decides to extend the period of the potential Technology Providers' responses submission so as to ensure the proper execution of the process.

**The questionnaire(s) to potential Technology Providers mainly contain(s) questions regarding:**

- Technical data of the offered solution or product.
- Their technical and professional capacity and experience in the execution of similar contracts of equivalent scope to the scope described herein.
- Their basic financial data.
- Their quality assurance system.
- Their reference list for successfully commercially delivered projects up to December 2025.

## 5 RFI Schedule Structure

It is noted that this invitation to participate in the RFI does not constitute an announcement of a Contract Award Process and does not imply the undertaking of any legal commitment or obligation on the part of either the participants or PPC.

### Contact Details

Participants should indicate contact details of persons responsible for providing information / clarifications for this Market Consultation / RFI

Name: .....

Phone Number: .....

Email: .....



Information regarding the participation process can be obtained from:

Name: Lydia Tsiaousi  
Phone Number: +30 2105292630  
Email: [l.tsiaousi@ppcgroup.com](mailto:l.tsiaousi@ppcgroup.com)

Market Consultation Invitation - RFI (Request for Information) **NGAPD-3004**

## Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.

	To be filled in	Units, type of response	Comment
<b>Financial</b>			
Company Turnover 2025		Euro	* Company to attach to this questionnaire the last three available audited financial statements.
Company Turnover 2024		Euro	
Company Turnover 2023		Euro	
Company Turnover 2022		Euro	<i>If 2025 data is yet unavailable</i>
<b>QA system</b>			
ISO 9001		yes/no	* Company to attach to this questionnaire the relevant certificate
ISO 18001		yes/no	* Company to attach to this questionnaire the relevant certificate
ISO 45001		yes/no	* Company to attach to this questionnaire the relevant certificate
<b>References</b>			
Reference units of Equipment of the Manufacturer in operation for Data Centers		Provide reference list	* referring only to type of equipment intended to be offered for the present project
<b>Scope of supply/services</b>			
<b>Critical Power Systems</b>			
Prefabricated LV Modules		yes/no	*Prefabricated Module provided by Single Manufacturer
Prefabricated MV Modules		yes/no	*Manufacturer can provide single equipment type or complete MV solution
Prefabricated Generators		yes/no	*Prefabricated Genset provided by Single Manufacturer
<b>Critical Cooling Systems</b>			
<b>Cloud Data Center (DC) Cooling</b>			
CRAH/Fan Wall Units		yes/no	*Manufacturer can provide single equipment type or complete cooling solution
Air-Cooled Chillers		yes/no	*Manufacturer can provide single equipment type or complete cooling solution
<b>AI Data Center (DC) Cooling</b>			
CDU		yes/no	*Manufacturer can provide single equipment type or complete cooling solution

**Market Consultation Invitation - RFI (Request for Information) NGAPD-3004****Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.**

	To be filled in	Units, type of response	Comment
Adiabatic Dry Coolers		yes/no	*Manufacturer can provide single equipment type or complete cooling solution
<b>Services</b>			
Installation/erection of the above		advisory services/ installation / erection / supervision services available in Greece	*Manufacturer can provide description of mandatory services for installation and commissioning of the equipment
Warrant/Commisioning/ set in operation		Supervision services available in Greece	*Manufacturer can provide description of services

## Market Consultation Invitation - RFI (Request for Information) NGAPD-3004

Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.

PREFABRICATED LV MODULE		
Requirement		Units, type of response
<b>PREFABRICATED MODULE: CONTAINER</b>		
Prefab Module	To be filled by Manufacturer	name of model & Manufacturer; Same manufacturer for prefab module and UPS attach standard documentation reference stating unified Manufacturer Solution
Site location	Aghios Demetrios Power Plant in Kozani	
Deployment	Outdoor	Requirement
Operating Ambient Temperature	-20...+45 C or as per ASHAE climatic design condition 2021 for n= 20 year or based on local environment conditions for 20 years extreme	Whichever is more stringent
Maintenance channel Illuminance	To be filled by Manufacturer	Lux level
Seismic Zone Performance	To be filled by Manufacturer	Zone
Protection level of entire system	To be filled by Manufacturer	Manufacturer to provide their Ingress Protection Level - IP
Color	To be filled by Manufacturer	RAL
Corrosion Protection (outdoor)	To be filled by Manufacturer	Tested as per ISO 12944-6 or equivalent (e.g. C4)
Fire Resistance	To be filled by Manufacturer	Provide fire resistance/rating of prefab module incl. fire resistance of roof, walls, doors, floor in minutes (min).
Indoor Flooring	To be filled by Manufacturer	No raised floor, raised floor
Maximum Dimensions Length x Width x Height	To be filled by Manufacturer	mm
Maximum Weight (tons)	To be filled by Manufacturer	tons
Room Partition	To be filled by Manufacturer	Single room module with batteries in the same room, separate battery room
Earthing	To be filled by Manufacturer	TN-S, TN-C-S
PE	To be filled by Manufacturer	Module earth bar and external connections
Main Distribution Board (MDB)	To be filled by Manufacturer	Incoming Amps range
SMDB-UPS-MECH	To be filled by Manufacturer	Incoming Amps range
UPS IT	To be filled by Manufacturer	MVA, Provide the typical UPS output ranges in MVA and the configuration of parallel UPS e.g 2,4MVA=2x1,2MVA UPS) for critical IT loads
UPS Mechanical	To be filled by Manufacturer	MVA, Provide the typical UPS output ranges in MVA and the configuration of parallel UPS e.g 300MVA=1x300MVA UPS) for critical mechanical loads
Module internal Cooling Technology	To be filled by Manufacturer	Direct Expansion (DX), Fans. Prefab module supported cooling type configurations such as DX, Fans etc. to be listed
AC Unit Capacity	To be filled by Manufacturer	Rated KW per AC unit
AC Unit Redundancy	To be filled by Manufacturer	N, N+1
Module internal Cooling Typical Flow Distribution	To be provided by Manufacturer	Typical Prefab Module CFD view to understand the cooling flow inside the module (e.g. separated cold/hot air or mixed in the same room etc.)
Internal Equipment Access and Maintenance Space	To be filled by Manufacturer	Front access and front maintenance
In - outgoing feeders	To be filled by Manufacturer	Busbars and/or cables
Cable/busbars entry/exit	To be filled by Manufacturer	From Top or Bottom
Interconnection between MDB & UPS	To be filled by Manufacturer	Busbars/Cables
Lithium Battery Technology	To be filled by Manufacturer	LFP, NMC etc.
Lithium Ion Battery Autonomy	To be filled by Manufacturer	min
Lead time DDP	To be filled by Manufacturer	Estimated weeks
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description
<b>References</b>		
Reference units of Prefabricated LVS+UPS Modules in operation for Data Centers	To be provided by Manufacturer	
Europe in last 5 years		number of units
Rest of the world in last 5 years		number of units
<b>LVS: MDB</b>		
Typical Input	To be filled by Manufacturer	Amps range
Form of Separation	Form 4b type 6	Requirement
Power Metering	To be filled by Manufacturer	Propose Power Meters for Input and Output and Level of Meters for each function
Short-circuit rating	To be filled by Manufacturer	KA/1sec, subject to calculations
IP of Switchgear	To be filled by Manufacturer	IPxx
UPS External Maintenance Bypass	Yes	Requirement
Interlock arrangement for UPS/External Maintenance Bypass	To be filled by Manufacturer	E.g. Castel key
UPS load Bank breaker	Yes	Requirement
Load bank Connection Panel	To be filled by Manufacturer	E.g. Camlock or equivalent connections for mobile load bank
<b>UPS</b>		
UPS Technology	Modular online double conversion transformless UPS	Requirement
Modular UPS	Hot-Swappable Power Modules	Requirement
UPS Power Module Step	To be provided by Manufacturer	KVA per Power Module within modular UPS frame
External Maintenance Bypass	Yes	Requirement
UPS Integrated Switches	To be provided by Manufacturer	Input/output/bypass/external bypass switches part of UPS
<b>AUXILIARIES</b>		
Fire System	To be filled by Manufacturer	Define supported room level fire systems
Fire System Special Considerations for Lithium Batteries	To be filled by Manufacturer	Provide proposal suitable for Lithium Batteries
Emergency lighting	To be filled by Manufacturer	Required
Access Control	To be filled by Manufacturer	E.g. exit door panic pushbar, mechanical door lock and door stopper etc.
EPMS Integration	To be filled by Manufacturer	Protocols
<b>Testing &amp; Commissioning</b>		
Factory Witness Test (FWT) for First of a Kind (FOK) at Manufacturer Location based on detailed protocol - L1	To be provided by Manufacturer	Submit Standard Manufacturer FWT standard procedure
Factory Acceptance Test (FAT) for Rest of a Kind based on standard factory test protocol	To be provided by Manufacturer	Submit Standard Manufacturer standard factory acceptance procedure
Site Acceptance and Commissioning Procedure L2-L4	To be provided by Manufacturer	Submit Standard Manufacturer standard acceptance & site commissioning procedure (per equipment) and which are mandatory to be offered by Manufacturer

## Market Consultation Invitation - RFI (Request for Information) NGAPD-3004

## Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.

## Prefab MV Modules

Site location	Aghios Demetrios Power Plant in Kozani	
Deployment	Outdoor	Requirement
Topology	MV rings with RMU and step down transformers	Manufacturer to advise on typical ring topology

## MV/LV Transformers - Tx

Equipment	To be filled by Manufacturer	name of model; name of manufacturer
Operating Ambient Temperature	-20...+45 C or as per ASHAE climatic design condition 2021 for n= 20 year or based on local environment conditions for 20 years extreme	whatever is more stringent
Seismic Performance	Site Location or better	
Type	To be filled by Manufacturer	Dry type / Oil Type
Cooling	To be filled by Manufacturer	AN, ONAN
Capacity	To be filled by Manufacturer	MVA range
Environmental, climatic and fire classes	To be filled by Manufacturer	E,C,F
Ingress Protection	To be filled by Manufacturer	
Color	To be filled by Manufacturer	IP-value
Arrangement	Delta-Star	Requirement
Vector symbol (HV/LV)	Dyn11	Requirement
Purpose	Step down	Requirement
Off-load Tap Changer	To be filled by Manufacturer	Define +/- %
Load k-factor	To be filled by Manufacturer	K-value (e.g. K1-3)
Winding Material MV/LV	To be filled by Manufacturer	Copper/Aluminium
Temperature Monitoring for winding and cable terminations	To be filled by Manufacturer	Provide proposal
Interconnection between Tx and MDB in Prefab LV Module	To be filled by Manufacturer	Cables/Busbars
Transformer Impedance (IEC 60076-5)	To be filled by Manufacturer	% value (e.g. 5%-12% etc.)
Length x Width x Height	To be filled by Manufacturer	mm
Maximum Weight	To be filled by Manufacturer	tons
Earthing	To be filled by Manufacturer	TN-S,TN-C-S
Lead time DDP	To be filled by Manufacturer	Estimated weeks
EPMS Integration	To be filled by Manufacturer	Supervision for integration of signals to EPMS
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description

## RMU

Equipment	To be filled by Manufacturer	name of model; name of manufacturer
Current Rating	To be filled by Manufacturer	Amps
GIS	Non-SF6 Gas Technology	Requirement
Fault Withstand Current	To be filled by Manufacturer	kA/sec
Internal Arc Classification	To be filled by Manufacturer	AFLR etc.
Internal arc maximum Value	To be filled by Manufacturer	kA for 3 sec
External enclosure IP	To be filled by Manufacturer	IP-value
Control Breakers	To be filled by Manufacturer	Remote/Local
MV cable Entry/Exit	To be filled by Manufacturer	Bottom etc.
Control Voltage and Control Back up	To be filled by Manufacturer	110VDC with BTU, 230AAC with UPS supply etc. Proposal for multiple RMU in a ring and multiple rings in the Data Center
Breakers/Switches	To be filled by Manufacturer	Feeder Control Units/Load Breaker Switches Provide Proposal
Protection Relay Functions	To be filled by Manufacturer	Manufacturer to advise
CT	To be filled by Manufacturer	Manufacturer to advise
VT	To be filled by Manufacturer	Manufacturer to advise
Lead time DDP	To be filled by Manufacturer	Estimated weeks
EPMS Integration	To be filled by Manufacturer	Supervision for integration of signals to EPMS
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description

**Market Consultation Invitation - RFI (Request for Information) NGAPD-3004****Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.****Enclosure or Module**

Outdoor Enclosure	To be filled by Manufacturer	In case equipment is not suitable for outdoor use (e.g. dry-type transformer etc.), MV Module enclosure is required and shall be provided. Provide proposal.
Define scope of prefab Enclosure	To be filled by Manufacturer	RMU / Tx Enclosures
Maintenance channel Illuminance	To be filled by Manufacturer	Lux level
Seismic Zone Performance	To be filled by Manufacturer	Zone
Protection level of entire system	To be filled by Manufacturer	Manufacturer to provide their Ingress Protection Level - IP
Color	To be filled by Manufacturer	RAL
Corrosion Protection (outdoor)	To be filled by Manufacturer	Tested as per ISO 12944-6 or equivalent (e.g. C4)
Fire Resistance	To be filled by Manufacturer	Provide fire resistance/rating of prefab module incl. fire resistance of roof, walls, doors, floor in minutes (min).
Indoor Flooring	To be filled by Manufacturer	No raised floor, raised floor
Maximum Dimensions Length x Width x Height	To be filled by Manufacturer	mm
Maximum Weight (tons)	To be filled by Manufacturer	tons
Room Partition	To be filled by Manufacturer	Single room module with batteries in the same room, separate battery room
PE	To be filled by Manufacturer	Module earth bar and external connections
Module internal Cooling Technology	To be filled by Manufacturer	Direct Expansion (DX), Chilled Water (CW), Fan. Prefab module supported cooling type configurations such as DX, Chilled Water, extraction fan etc.to be listed
CRAC/CRAH Capacity	To be filled by Manufacturer	Rated KW per CRAC/CRAH
CRAC/CRAH Redundancy	To be filled by Manufacturer	N+1
Fire System	To be filled by Manufacturer	Define supported room level fire systems
Emergency lighting	To be filled by Manufacturer	Required
Access Control	To be filled by Manufacturer	E.g. exit door panic pushbar, mechanical door lock and door stopper etc.
Lead time DDP	To be filled by Manufacturer	Estimated weeks
EPMS Integration	To be filled by Manufacturer	Supervision for integration of singals to EPMS
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description

**Testing & Commissioning**

Factory Witness Test (FWT) for First of a Kind (FOK) at Manufacturer Location based on detailed protocol - L1	To be provided by Manufacturer	Submit Standard Manufacturer FWT standard procedure (per equipment and per module)
Factory Acceptance Test (FAT) for Rest of a Kind based on standard factory test protocol	To be provided by Manufacturer	Submit Standard Manufacturer standard factory acceptance procedure (per equipment and per enclosure)
Site Acceptance and Commisioning Procedure L2-L4	To be provided by Manufacturer	Submit Standard Manufacturer standard acceptance & site commissioning procedure (per equipment) and which are mandatory to be offered by Manufacturer

## Market Consultation Invitation - RFI (Request for Information) NGAPD-3004

## Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.

## Prefabricated Generators - On Premise - Emergency Back-up

Site location	Aghios Demetrios Power Plant in Kozani	
Deployment	Outdoor	Requirement
Equipment	To be filled by Manufacturer	name of model; name of manufacturer
Deployment	Outdoor	Requirement
Operating Ambient Temperature	-20...+45 C or as per ASHAE climatic design condition 2021 for n= 20 year or based on local environment conditions for 20 years extreme	whatever is more stringent
Seismic Zone Performance	To be filled by Manufacturer	Zone for Site Location or better
Uptime Institute Tier Level	Tier 3	Requirement
Rating	DCC rating	Requirement
Purpose	Onsite back up power in case of power outage	Requirement
Fuel	To be filled by Manufacturer	Manufacturer to advise on fuel type
Fuel System and Autonomy	To be filled by Manufacturer	Manufacturer to advise on onsite fuel storage for Tier 3 Uptime, EN50600/ISO/IEC22237 Class 3 requirements, fuel lines, filtration, polishing, leak detection, day tanks
Fuel Polishing	To be filled by Manufacturer	Manufacturer to advise
Design Topology and arrangement for complete Data Center Back up	To be filled by Manufacturer	Manufacturer to advise a topology solution for 300MWIT Data Center genset power solution. E.G. Parallel MV gensets or LV Distributed Redundancy etc. Provide as basic schematic for Tier 3 solution including proposed redundancy
Type	To be filled by Manufacturer	Manufacturer to Advise Open Type or Containerized genset
Cooling	To be filled by Manufacturer	Manufacturer to advise
Capacity	To be filled by Manufacturer	DDC MW rating
Min stable load	To be filled by Manufacturer	MW
Ingress Protection	To be filled by Manufacturer	IP
Color	To be filled by Manufacturer	RAL
Engine Performance	To be filled by Manufacturer	value in sec to take over 100% load
Start-up time (max)	To be filled by Manufacturer	value in sec
Full load time (max)	To be filled by Manufacturer	value in sec to take over 100% load
Additional requirements for startup at lower ambient temperature (down to -20 °C)	To be filled by Manufacturer	Manufacturer to advise
Total Gross Heat rate at nominal load	To be filled by Manufacturer	GJ/MWh
Total Gross electrical eff. at nominal load	To be filled by Manufacturer	%
Heat rate at 50% of nominal load	To be filled by Manufacturer	GJ/MWh
Gross electrical eff. at 50% of nominal load	To be filled by Manufacturer	%
Ramp up	To be filled by Manufacturer	MW/min
Ramp down	To be filled by Manufacturer	MW/min
Short circuit	To be filled by Manufacturer	Manufacturer to provide typical short circuit decrement curves
Frequency Recovery time	To be filled by Manufacturer	Maximum sec
Frequency Stability (steady)	To be filled by Manufacturer	value +/- %
Frequency Stability (transient)	To be filled by Manufacturer	value +/- %
Voltage Regulation (steady)	To be filled by Manufacturer	value +/- %
Voltage Regulation (transient)	To be filled by Manufacturer	value +/- %
Noise level and compliance with requirements	To be filled by Manufacturer	dB level and Manufacturer to advise on acoustic enclosure and exhaust silencing
Emissions and compliance with requirements	To be filled by Manufacturer	Manufacturer to advise, EU standards compliance (EU Stage V (EU), and ISO 8178)
Cooling	To be filled by Manufacturer	Manufacturer to advise related genset cooling but not limited to Radiator, coolant temperature control, airflow management, cooling medium
Fire System & Ventilation	To be filled by Manufacturer	Manufacturer to advise
Control & Monitoring	To be filled by Manufacturer	Manufacturer to advise
Fuel System and Autonomy	To be filled by Manufacturer	Onsite fuel storage for Tier 3 Uptime, EN50600/ISO/IEC22237 Class 3 requirements, fuel lines, filtration, polishing, leak detection, day tanks
Fuel Polishing	To be filled by Manufacturer	Manufacturer to advise
Length x Width x Height	To be filled by Manufacturer	mm
Maximum Weight	To be filled by Manufacturer	tons
Lead time DDP	To be filled by Manufacturer	Estimated weeks
EPMS Integration	To be filled by Manufacturer	Supervision for integration of signals to EPMS
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description

## Enclosure or Module

Outdoor Enclosure	To be filled by Manufacturer	For Containerized gensets
Protection level of entire system	To be filled by Manufacturer	Manufacturer to provide their Ingress Protection Level - IP
Color	To be filled by Manufacturer	RAL
Corrosion Protection (outdoor)	To be filled by Manufacturer	Tested as per ISO 12944-6 or equivalent (e.g. C4)
Fire Resistance	To be filled by Manufacturer	Provide fire resistance/rating of prefabricated module incl. fire resistance of roof, walls, doors, floor in minutes (min).
Maximum Dimensions Length x Width x Height	To be filled by Manufacturer	mm
Maximum Weight (tons)	To be filled by Manufacturer	tons
Cooling System	To be filled by Manufacturer	Manufacturer to provide information for cooling design, capacity and redundancy
Fire System	To be filled by Manufacturer	Define supported room level fire systems
Access Control	To be filled by Manufacturer	E.g. exit door panic pushbar, mechanical door lock and door stopper etc.
EPMS Integration	To be filled by Manufacturer	Supervision for integration of signals to EPMS

**Market Consultation Invitation - RFI (Request for Information) NGAPD-3004****Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.**

Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description
<b>Testing &amp; Commissioning</b>		
Factory Witness Test (FWT) for First of a Kind (FOK) at Manufacturer Location based on detailed protocol - L1	To be provided by Manufacturer	Submit Standard Manufacturer FWT standard procedure
Factory Acceptance Test (FAT) for Rest of a Kind based on standard factory test protocol	To be provided by Manufacturer	Submit Standard Manufacturer standard factory acceptance procedure
Site Acceptance and Commissioning Procedure L2-L4	To be provided by Manufacturer	Submit Standard Manufacturer standard acceptance & site commissioning procedure (per equipment) and which are mandatory to be offered by Manufacturer

**Market Consultation Invitation - RFI (Request for Information) NGAPD-3004****Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.****Cloud DC Cooling**

Site location	Aghios Demetrios Power Plant in Kozani	
<b>FWU</b>		
Equipment	To be filled by Manufacturer	name of model; name of Manufacturer
Deployment	Indoor in Data Hall	
Type of CRAH Unit for Hyperscale Data Center	Fan Wall Units (FWU)	Requirement
Cooling medium	High Temperature Chilled Water	Requirement
Design Modularity	Modular	Requirement
Cooling Capacity	To be filled by Manufacturer	Rated KW range
Air flow Directions	Horizontal	No raised floor
Quantity of Fans	To be filled by Manufacturer	number
Supply Water temperature	To be filled by Manufacturer	C
Return Water temperature	To be filled by Manufacturer	C
Fan Type	To be filled by Manufacturer	EC Fans
Full Load THDi	To be filled by Manufacturer	< value %
Power factor	To be filled by Manufacturer	value
Dual/Single Power Supply	To be filled by Manufacturer	In case of dual power supply define typical automatic transfer time or cooling interruption during power switch
Equipment Communication Protocols	To be filled by Manufacturer	
Air flow rate	To be filled by Manufacturer	m3/h
Power Supply	To be filled by Manufacturer	V/Ph/Hz
Rated Power	To be filled by Manufacturer	KW
Air Filter Class	To be filled by Manufacturer	
Dimensions Length x Width x Height	To be filled by Manufacturer	mm
Weight	To be filled by Manufacturer	kg
Lead time DDP	To be filled by Manufacturer	Estimated weeks
EPMS Integration	To be filled by Manufacturer	Supervision for integration of singals to EPMS
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description

**Air-cooled Chillers**

Equipment	To be filled by Manufacturer	name of model; name of Manufacturer
Deployment	Outdoor	Requirement
Operating Ambient Temperature	-20...+45 C or as per ASHAE climatic design condition 2021 for n= 20 year or based on local environmnnet consitions for 20 years extreme	whatever is more stringent
Color	To be filled by Manufacturer	RAL
Type of Chiller for Hyperscale Data Center	Air-cooled Chiller	Requirement
Free Cooling	To be filled by Manufacturer	
Cooling Operation Supported	To be filled by Manufacturer	Hybrid etc.
Topology	Concurrently Maintenance Ring N+1	Manufacturer to advise on alternatives
Cooling medium	To be filled by Manufacturer	Provide antifreeze chilled water mixture
Variable Speed Drive Chiller	Yes	Requirement
Cooling Capacity	To be filled by Manufacturer	Rated KW range
Refrigerant	To be filled by Manufacturer	
Cooling System & Buffer Tanks for Continuous Cooling	To be filled by Manufacturer	Manufacturer to advise on solution for typical 8-10MW IT DH
Supply Water temperature	To be filled by Manufacturer	Celsius
Return Water temperature	To be filled by Manufacturer	Celsius
Electrical Scheme	To be filled by Manufacturer	Provide single line diagram
Power Consuption	To be filled by Manufacturer	kW
Noise levels	To be filled by Manufacturer	dB
IP Protection	To be filled by Manufacturer	IP value
Lead time DDP	To be filled by Manufacturer	Estimated weeks
EPMS Integration	To be filled by Manufacturer	Supervision for integration of singals to EPMS
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description

**Market Consultation Invitation - RFI (Request for Information) NGAPD-3004****Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.****Testing & Commissioning**

Factory Witness Test (FWT) for First of a Kind (FOK) at Manufacturer Location based on detailed protocol - L1	To be provided by Manufacturer	Submit Standard Manufacturer FWT standard procedure (per equipment)
Factory Acceptance Test (FAT) for Rest of a Kind based on standard factory test protocol	To be provided by Manufacturer	Submit Standard Manufacturer standard factory acceptance procedure (per equipment)
Site Acceptance and Commissioning Procedure L2-L4	To be provided by Manufacturer	Submit Standard Manufacturer standard acceptance & site commissioning procedure (per equipment) and which are mandatory to be offered by Manufacturer

## Market Consultation Invitation - RFI (Request for Information) NGAPD-3004

## Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.

**AI DC Cooling**

Site location	Aghios Demetrios Power Plant in Kozani	
<b>CDU</b>		
Equipment	To be filled by Manufacturer	name of model; name of Manufacturer
Deployment	Indoor	Manufacturer to advise on installation inside or outside Data Hall
Type of Coolign Unit	Coolant Distribution Units (CDU)	Requirement
Design Modularity	Modular	Requirement
Cooling Capacity	To be filled by Manufacturer	Rated KW range
Pump type	To be filled by Manufacturer	
Quantity of Water Pumps	To be filled by Manufacturer	number
Primary Side supply/return liquid rated temperature	To be filled by Manufacturer	C
Secondary Side supply/return liquid rated temperature	To be filled by Manufacturer	C
Water Flow on secondary side	To be filled by Manufacturer	L/min
Available lift on secondary side	To be filled by Manufacturer	kPa
Primary side liquid medium	To be filled by Manufacturer	
Secondary side liquid medium	To be filled by Manufacturer	
Pipe routing mode	To be filled by Manufacturer	Bottom/top
Precision of filter on primary side	To be filled by Manufacturer	mesh
Precision of filter on secondary side	To be filled by Manufacturer	mesh
Full Load THDI	To be filled by Manufacturer	< value %
Power factor	To be filled by Manufacturer	value
Dual/Single Power Supply	To be filled by Manufacturer	In case of dual power supply define typical automatic transfer time or cooling interruption during power switch
Equipment Communication Protocols	To be filled by Manufacturer	
Power Supply	To be filled by Manufacturer	V/Ph/Hz
Rated Power	To be filled by Manufacturer	KW range
Dimensions Length x Width x Height	To be filled by Manufacturer	mm
Weight	To be filled by Manufacturer	kg
In Room Level Cooling	To be filled by Manufacturer	Manufacturer to advise on solution for typical AI load Room level cooling (e.g. rear door heat exchangers, In Room Chilled Water Cooling)
Lead time DDP	To be filled by Manufacturer	Estimated weeks
EPMS Integration	To be filled by Manufacturer	Supervision for integration of singals to EPMS
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description

**Adiabatic Dry Coolers**

Equipment	To be filled by Manufacturer	name of model; name of Manufacturer
Deployment	Outdoor	Requirement
Operating Ambient Temperature	-20...+45 C or as per ASHAE climatic design condition 2021 for n= 20 year or based on local environmnet consitions for 20 years extreme	whatever is more stringent
Color	To be filled by Manufacturer	RAL
Type of Chiller for Hyperscale Data Center	Adiabatic Dry Cooler	Requirement
Free cooling	To be filled by Manufacturer	
Topology	Concurrently Maintenance Ring N+1	Manufacturer to advise on alternatives
Fluid type	To be filled by Manufacturer	
Flow rate	To be filled by Manufacturer	m3/h
Cooling Capacity	To be filled by Manufacturer	Rated KW range
Cooling System & Redundant Water Tanks for Continuous Cooling	To be filled by Manufacturer	Manufacturer to advise on solution for typical 18-20 MW IT DH
Supply Water temperature	To be filled by Manufacturer	Celsius
Return Water temperature	To be filled by Manufacturer	Celsius
Coil pressure drop	To be filled by Manufacturer	kPa
IP Protection	To be filled by Manufacturer	IP value
Noise levels	To be filled by Manufacturer	dB
Lead time DDP	To be filled by Manufacturer	Estimated weeks

**Market Consultation Invitation - RFI (Request for Information) NGAPD-3004****Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece.**

EPMS Integration	To be filled by Manufacturer	Supervision for integration of singals to EPMS
Technical Datasheet	To be provided by Manufacturer	Standard Product/Solution Series Datasheet
Product/Solution Description	To be provided by Manufacturer	Standard Product/Solution Series Description
<b>Testing &amp; Commissioning</b>		
Factory Witness Test (FWT) for First of a Kind (FOK) at Manufacturer Location based on detailed protocol - L1	To be provided by Manufacturer	Manufacturer FWT standard procedure (per equipment)
Factory Acceptance Test (FAT) for Rest of a Kind based on standard factory test protocol	To be provided by Manufacturer	Manufacturer standard factory acceptance procedure (per equipment)
Site Acceptance and Commisioning Procedure L2-L4	To be provided by Manufacturer	Submit Standard Manufacturer standard acceptance & site commissioning procedure (per equipment) and which are mandatory to be offered by Manufacturer

## NON-DISCLOSURE AGREEMENT

This Non-Disclosure Agreement (the “**Agreement**”) is entered into as of [●], 2026 (the “**Effective Date**”) between

- a) **Public Power Corporation SA**, a company organized and existing under the laws of Greece, having its registered seat at 30 Chalkocondili str., Athens, Greece, duly represented herein by its Chief Procurement Officer, Ms. Georgia Christodouloupolou, hereinafter referred to as “**PPC**”; and
- b) [●], a company organized and existing under the laws of [●], having its registered seat at [●], duly represented herein by [●], hereinafter referred to as “[●]”.

These parties may also be referred to individually as “**Party**” or collectively as “**Parties**”, and each of them is a “**Receiving Party**” when it receives Confidential Information (as defined below) from the other Party and a “**Disclosing Party**” when it discloses Confidential Information to the other Party.

### Article 1

#### Disclosure of Confidential Information

In connection with RFI NGAPD-3004 for the Critical MEP Equipment for the Colocation Hybrid Data Centre at the Aghios Demetrios Power Plant, Kozani – Greece (the “**Purpose**”) and during the term of this Agreement, each Party is willing to exchange Confidential Information, in accordance with the terms and conditions of this Agreement.

“**Confidential Information**” means: (i) information relating to the Purpose which may include commercial, financial, scientific, engineering and/or technical data, contractual terms and conditions, bid information, and other information, data, knowledge, and know-how; (ii) the fact that discussions and evaluations are taking place to pursue the Purpose, the Parties’ participation in such discussions and evaluations, their nature and/or contents and the existence of this Agreement and its contents.

For the avoidance of doubt, Confidential Information includes information in whatever form and however communicated (whether orally, in writing, in electronic or other tangible form, or by inspection) by the Disclosing Party or by its Authorized Persons (as defined in Article 4), and regardless of whether it is labeled as confidential or not, and includes information generated by the Receiving Party or by an Authorized Person that is derived in whole or in part from the information exchanged.

### Article 2

#### Undertaking not to Disclose

In consideration of the exchange of Confidential Information, the Receiving Party shall:

- (a) use the Confidential Information exclusively for the Purpose, unless otherwise expressly agreed to in writing by the Disclosing Party;
- (b) not disclose the Confidential Information to anyone without the prior written consent of Disclosing Party, except as provided in this Agreement; and
- (c) treat the Confidential Information with the same degree of care as it employs for its own equally important confidential information to avoid disclosure to any third party, but at least with reasonable care.

(d) not use, directly or indirectly, the Confidential Information for its own benefit, indicatively for the acquisition or transfer of PPC's shares, or for any act constituting a breach of the Stock Exchange legislation. [●] acknowledges that access by it or its Authorized Persons Participants to the Confidential Information may provide it or them with Inside Information concerning PPC, which has not been publicly disclosed. [●] is prohibited from disclosing such Inside Information to any third party in violation of this Agreement. [●] acknowledges that [●] and its Authorized Persons are aware of such laws and agree to fully comply with such laws.

## Article 3

### Exceptions to Confidentiality Obligation

3.1 The following shall not constitute Confidential Information:

- (a) prior to its disclosure by the Disclosing Party to the Receiving Party, it was already known to the Receiving Party (not as a result of a breach of any duty or obligation towards the Disclosing Party) provided that immediately upon the disclosure by the Disclosing Party, the Receiving Party will bring such fact to the attention of the Disclosing Party; or
- (b) is at the time of disclosure in the public domain or which becomes public domain in each case, where the publication making such information public domain is not the result of a breach of this Agreement; or
- (c) is legally received from a third party where the Receiving Party has no reasonable cause to believe that the receipt or the disclosure of such information by such third party was the result of or constitutes a breach of any duty or obligation towards the Disclosing Party; or
- (d) is independently developed by the Receiving Party without any reference to the Confidential Information and by employees who did not have any access to it.

3.2 It shall not be a breach of this Agreement if the Receiving Party or its Authorized Persons disclose the Confidential Information to the extent it is required to disclose the Confidential Information under applicable law, rule or regulation or any legal, judicial, governmental, administrative or regulatory order, authority or process, provided that, subject to any applicable legal prohibitions, the Receiving Party shall make all reasonable efforts to give prompt written notice to the Disclosing Party prior to such disclosure to allow the Disclosing Party to seek a protective order or other relief as appropriate (for the avoidance of doubt, disclosure in the absence of an obligation to disclose shall not constitute an authorized disclosure under this paragraph).

3.3. The burden of proof that Confidential Information which is disclosed resides within one of the exceptions set forth in this clause 3, shall be on the Receiving Party. The Receiving Party shall maintain the confidentiality of the Confidential Information until the Receiving Party has by clear and convincing evidence demonstrated to the Disclosing Party the validity of the aforesaid exceptions. In the event of a dispute between the Parties regarding the applicability of one of the exceptions set forth in this clause 3, the Receiving Party shall maintain the confidentiality of the Confidential Information until a final and non-appealable arbitration award and/or a final non-appealable court judgment is granted.

## Article 4

### Disclosure to Authorized Persons

4.1 The Receiving Party may disclose Confidential Information without the prior written consent of the Disclosing Party to the following persons and/or entities ("Authorized Persons") to the extent that the Receiving Party needs them to pursue the Purpose or any transaction between the Parties in relation to the Purpose, makes them aware that the Confidential

Information must be kept confidential, and requires them to keep the information confidential:

- (a) the directors, officers, and employees of the Receiving Party;
- (b) Affiliates of the Receiving Party and their directors, officers, and employees;

(“**Affiliate**” means, with respect to any legal entity, any legal entity directly or indirectly controlling, controlled by or under common control with, such other legal entity, but such legal entity shall be deemed to be an Affiliate only so long as such control exists. For purposes of this definition, “**control**” when used with respect to any legal entity, means the possession, directly or indirectly, of the power to cause the direction of management and/or policies of such legal entity, whether through the ownership of voting securities by contract or otherwise);

- (c) any outside legal counsel, consultant, or other agent retained by the Receiving Party or its Affiliate; or

## Article 5

### Obligation with Respect to Authorized Persons

The Receiving Party shall be responsible to the Disclosing Party for any breach of the confidentiality obligations by the Authorized Persons.

## Article 6

### Destruction or Return of Confidential Information

- 6.1 The Disclosing Party may demand the destruction of the Confidential Information at any time upon giving written notice to Receiving Party. Within thirty (30) days of receipt of such notice, the Receiving Party, at its cost, shall, at its option, return or destroy all of the Disclosing Party’s Confidential Information in its possession and shall direct that its Authorized Persons return or destroy Confidential Information in their possession, except as provided in Clause 6.2. The Parties agree that upon the Disclosing Party’s request, the Receiving Party will sign a certificate confirming the return or destruction of all the Confidential Information.
- 6.2 Notwithstanding Clause 6.1, the Receiving Party or its Authorized Persons may retain:
  - (a) Confidential Information that is required by applicable law, regulation, or by *bona fide* document retention and compliance policies, to be retained by it, including any Confidential Information in any legal advice, internal working papers, legal opinions, legal due diligence reports prepared for the Receiving Party and minutes of meetings of the board of directors of the Receiving Party;
  - (b) any automatically generated backups or archive copies of Confidential Information located on an off-site server as a result of the automatic back-up of data in the usual operations of the Receiving Party; and
  - (c) any electronic copies of Confidential Information that are not reasonably practicable for the Receiving Party to return or destroy in accordance with Clause 6.1.
- 6.3 The Receiving Party's compliance with this Clause 6 does not release it from any of its other obligations under this Agreement and this Clause 6 survives the expiry or termination of this Agreement as provided for in clause 7.

## **Article 7**

### **Term**

This Agreement has a term of two years from the Effective Date. The confidentiality obligations shall remain in effect for Confidential Information retained after the aforementioned 2-year period until the date such Confidential Information is destroyed or returned to the Disclosing Party.

## **Article 8**

### **Representations and Warranties**

- 8.1 The Disclosing Party represents and warrants that it either owns the Confidential Information disclosed by it or otherwise has the right and authority to disclose the Confidential Information to the Receiving Party.
- 8.2 The Disclosing Party, however, makes no representations or warranties express or implied, as to the quality, accuracy and completeness of the Confidential Information. The Disclosing Party and its Authorized Persons will have no liability whatsoever with respect to the use of or reliance upon the Confidential Information by the Receiving Party (or its Authorized Persons).
- 8.3 The Receiving Party represents that disclosure of Confidential Information by the Disclosing Party to the Receiving Party does not create any conflict of interest, otherwise the Receiving Party must inform promptly and in writing the Disclosing Party if any conflict of interest arises or may arise during this Agreement.

## **Article 9**

### **Ownership and Licenses**

- 9.1 The Receiving Party shall acquire no proprietary interest in or right to the Confidential Information of the Disclosing Party.
- 9.2 Other than the license to use the Confidential Information in connection with the Purpose as expressly set out in this Agreement, neither Party conveys to the other Party, any other licenses or any other rights such as, but not limited to, patents, utility models, trademarks or tradenames, nor does this Agreement constitute any obligation of the Disclosing Party to grant or convey such rights to the Receiving Party. The Receiving Party shall not undertake any reverse engineering or replication or any similar act intended for the replication of any products containing Confidential Information unless specifically authorized in writing to do so by the Disclosing Party. The Receiving Party shall not be entitled to file for patents or other statutory protection in any country based on or using any Confidential Information received hereunder, and any such patent or statutory protection must be transferred to the Disclosing Party upon its request and without any charge. The disclosure of Confidential Information does not constitute any right of prior use for the Receiving Party.

## **Article 10**

### **Governing Law and Dispute Resolution**

- 10.1 This Agreement shall be governed by and interpreted in accordance with the substantive laws of Greece excluding any choice of law rules which would refer the matter to the laws of another jurisdiction.

- 10.2 Any dispute, controversy or claim arising out of or relating to this Agreement (including any question regarding its existence, validity or termination) (a “**Dispute**”) shall be referred to and finally resolved by the Courts of Athens.
- 10.3 The Parties acknowledge that there would be no adequate remedy at law if the Receiving Party failed to perform or threatened to breach any of its obligations in this Agreement and that any such failure may result in material irreparable injuries to the Disclosing Party and that it will not be possible to measure damages for such injuries precisely, and, accordingly the Parties agree that the Disclosing Party, in addition to any other remedy to which it may be entitled at law or in equity, shall be entitled to seek specific performance of the obligations of the Receiving Party under this Agreement in accordance with the terms and conditions of this Agreement. Accordingly, the Receiving Party consents to the enforcement of this Agreement by specific performance or injunctive relief without proof of actual damages.

## Article 11

### Notices

All notices authorized or required between the Parties by any of the provisions of this Agreement shall be in written English, properly addressed to the other Party as shown below, and delivered in person, by courier, or by e-mail. Oral communication does not constitute notice for purposes of this Agreement. A notice given under any provision of this Agreement shall be deemed delivered only upon actual delivery of the notice to the physical or electronic address of the Party shown below.

### PPC

Address: 25, Patision st., Athens GR-104 32

Attention: Mr. Antonios – Athanasios Mylonas

e-mail: anto.mylonas@ppcgroup.com

cc: a.soumelidis@ppcgroup.com

[•]

Address: [•]

Attention: [•]

e-mail: [•]

## Article 12

### No Assignment - Successors

- 12.1 Neither this Agreement nor any rights and obligations under this Agreement may be assigned or delegated by either Party without the prior written consent of the other Party.
- 12.2 This Agreement shall be binding upon the Parties’ respective successors and permitted assigns.

## **Article 13**

### **General Provisions**

- 13.1 No waiver by either Party of any one or more breaches of this Agreement by the other Party shall operate or be construed as a waiver of any future default or defaults by the same Party. Neither Party shall be deemed to have waived, released, or modified any of its rights under this Agreement unless such Party has expressly stated, in writing, that it does waive, release or modify such rights.
- 13.2 This Agreement may not be modified except by written consent of the Parties.
- 13.3 If one or more provisions of this Agreement are, or become entirely or partially invalid or unenforceable, then this shall not affect the validity or enforceability of the remaining provisions of this Agreement. The foregoing shall also apply if the Agreement contains any regulatory gaps. Instead of the invalid or unenforceable provisions, or in order to close the gaps, a rule shall be used, which, in so far as it is legally permissible and as closely as possible reflects the intentions of the Parties concluding the Agreement or, considering the meaning and purpose of the Agreement, effects the purpose of the Agreement, had they considered the points at the time of concluding the Agreement.
- 13.4 This Agreement comprises the full and complete agreement of the Parties regarding the disclosure of the Confidential Information and supersedes and cancels all prior communications, understandings, and agreements between the Parties relating to the Confidential Information, whether written or oral, expressed or implied.
- 13.5 The terms of this Agreement shall control over any additional purported confidentiality requirements imposed by any offering memorandum, web-based database or similar repository of Confidential Information to which Receiving Party or its Authorized Persons is granted access in connection with this Agreement or the Purpose, notwithstanding acceptance of such an offering memorandum or submission of an electronic signature, “clicking” on an “I Agree” icon or other indication of assent to such additional confidentiality conditions.
- 13.6 This Agreement is not a contractual undertaking to pursue the Purpose or enter into any further agreements (e.g. purchase and sales, joint ventures, cooperation etc.) but rather is merely intended to give each Party access to the information concerning the Purpose.
- 13.7 Nothing herein shall be construed as creating between the Parties the relationship of a partnership, joint venture or other joint enterprise.
- 13.8 This Agreement may be executed in several counterparts, each of which shall be deemed an original, but all of which together shall constitute one and the same instrument. To the extent permitted by law, electronic signatures or a manual signature whose image shall have been transmitted electronically will constitute an original signature for all purposes. The delivery of copies of this agreement, including executed signature pages, by electronic transmission will constitute effective delivery of this agreement for all purposes.

## **Article 14**

### **Ethics and Anticorruption**

PPC declares that in managing its business activities and its relationships, it adheres to the principles contained in PPC Code of Conduct and other policies such as anti-bribery, human right protection, as subsequently amended and supplemented all of them available at [www.ppcgroup.com](http://www.ppcgroup.com) PPC wishes its counterparties refer to the same principles in managing their business activities and their relationships.

## Article 15

### Data protection

15.1 For the purposes of this Agreement, all the definitions related to personal data herein contained have the meanings set out in European Regulation no. 679/2016 (hereinafter the “GDPR”) and in any other applicable legislation.

Any personal data provided by each Party in connection with this Agreement has or shall be provided only in compliance with, and may be collected and processed by, the other Party only in accordance with the provisions of the GDPR and any other applicable legislation. Personal data will be processed automatically and/or in paper form and will be stored for the entire duration of the Agreement and for no longer than permitted by applicable laws.

15.2 The Parties may collect and process personal data only for purposes strictly related to the Purpose and may share the personal data with Affiliates within the frame of the Purpose.

15.3 Personal data shall not be communicated and/or disclosed to third parties other than if appointed as data processor and in the cases allowed by the law.

15.4 The data controller of the personal data collected and processed by PPC and the data protection officer (“DPO”) of PPC is available at the following address: [●]

The data controller of the personal data collected and processed by [●] and the data protection officer (“DPO”) of [●] is available at the following address: [●].

15.5 Any data subject whose personal data has been collected or processed pursuant to this Agreement may exercise the rights provided by articles 15-21 of GDPR (such as the right to access to and rectification or erasure of personal data, right to restriction or to object to processing as well as the right to data portability) by writing to the relevant Party.

The Parties sign this agreement, intending to be bound and acknowledging that each of the clauses has been the object and result of negotiations.

For PPC

For [●]

---

By: Ms. Georgia Christodoulou  
Title: Chief Procurement Officer

---

By:  
Title: